

3Ø, 250Vac (30/40/50/60A) : 삼상 교류 250V 고감쇄형 BTM-2***-MS Series (High Atten. type)



■ Features

- High attenuation
- Multi stage
- Dual PE system
- Light weight
- Low cost


■ Typical Applications

- General purpose
- Industrial equipment
- Motor drive equipments
- AVR, UPS, Inverter, Converter
- Factory automation equipment
- Three-phase electricity supply
- ACB Panel, distribution Panel



■ Technical specifications

Items	BTM-2030-MS	BTM-2040-MS	BTM-2050-MS	BTM-2060-MS
Rated Voltage (V _R)	3Ø, 250Vac			
Operating frequency	50 / 60Hz			
Rated Currents @40°C (I _R)	30A	40A	50A	60A
Withstanding voltage test	Line to Earth : 2,121Vdc for 1min, or 2,750Vdc for 2sec. (BHSTD-QUA-Q201)			
Insulation resistance	500Vdc for 1min. 300MΩ Min. (BHSTD-QUA-Q202)			
Leakage current	3.5mA Max. at rated voltage (BHSTD-QUA-Q203)			
Voltage drop	1.5V Max. (BHSTD-QUA-Q204)			
Temperature range	25/100/21 (-25°C to +100°C), 20~95% RH at Operating & Storage			
Designed according to	IEC/EN 60939 / UL1283 / CSA 22.2 No.8			
Weight [kg] (Max.)	2.45	2.40	2.41	2.40


■ Circuit Diagram



■ Shape & Dimension (mm)



■ Derating Curve



■ Lug ring terminal



■ Recommended torque

4.0 ~ 4.9 N · m