

REACTORS

Reactors for Hoist (호이스트용)

BHSA Series







Technical Specifications

Line Voltage	220V / 380V / 440V
Operating Frequency	50/60Hz
Insulation Class	H Class
Standard	IEC, KS C

Typical Applications

Hoist etc.



TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN

Selection Table

Type (형식명)	Specification(사양)		Dimension (외형치수, mm)						Weight (kg)	Remark
	Line Voltage(V)	Cap.(kW)	W	D	H	a	b	ØA×B		
BHSA - 1.5	440V	1.5	138	98	126	103	48	6×10	2.3	Fig.1
- 3	/	3	156	119	145	119	75	8×15	4.81	
- 4.4	380V	4.4	190	128	169	140	75	7×13	6.85	
- 7.5	/	7.5	190	153	169	140	100		9.5	

TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN