

1Ø Noise Cut Transformers (단상 NCT)

BHNCT-HC Series







Technical Specifications

Primary Voltage	208V / 220V
Secondary Voltage	208V / 220V
Operating Frequency	50/60Hz
Insulation Class	H Class
Standard	EN61558-2-4
※ 1MHz → Over -80dB	

Typical Applications

- Semi-conductor manufacture, Display power equipment
- Broadcasting audio-visual devices, Medical devices
- Controller systems(PLC, Robot, DCS etc.)
- Rail network, Subway to surge influence
- Transportation network signal control etc.



TO THE WORLD BUMHAN • WE MAKE FOR YOU • TO THE WORLD BUMHAN • WE MAKE FOR YOPU • TO THE WORLD BUMHAN • WE MAKE FOR YOU • TO THE WORLD BUMHAN

Selection Table

Type (형식명)	Specification(사양)			Dimension (외형치수, mm)						Weight (kg)	Remark
	Pri.(V)	Sec.(V)	Cap.(VA)	W	D	H	a	b	ØAxB		
BHNCT-HC500	208V 0	208V 0	500	157	160	144	130	115	7×27	13	Cable type (2.0m)
-HC1K			1k	186	190	166	160	135	7×34	19.5	Cable type (2.5m)
-HC1.5K			1.5k	186	201	166	160	145		22	Terminal block type
-HC2K	/	/	2k	224	230	192	192	160	7×40	32	
-HC3K	220V 0	220V 0	3k	248	280	210	213	190	8×45	44	
-HC5K			5k	275	340	233	238	230	8×50	63	
-HC7.5K			7.5k	314	370	268	270	250	8×60	91	

TO THE WORLD BUMHAN • WE MAKE FOR YOU • TO THE WORLD BUMHAN • WE MAKE FOR YOPU • TO THE WORLD BUMHAN • WE MAKE FOR YOU • TO THE WORLD BUMHAN