


## Reactors for Motor Starting[LV] (모터기동용 리액터 저압)

### BHSTRA-L Series







#### Technical Specifications

Line Voltage	220V / 380V / 440V
Operating Frequency	60Hz
Cooling System	Dry
Insulation Class	B Class

#### Typical Applications

Motor starting etc.



TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN

### Selection Table

Type (형식명)	Specification(사양)		Dimension (외형치수, mm)						Weight (kg)	Remark
	Line Voltage(V)	Cap.(kW)	W	D	H	a	b	ØA×B		
BHSTRA -20L	440V / 380V / 220V	15	331	325	327	200	194	13×30	25	
-25L		18.5	331	330	327	200	200		27	
-30L		22	351	330	348	200	200		30	
-40L		30	351	330	371	200	200		35	
-50L		37	371	340	371	220	210		38	
-60L		45	371	340	371	220	210		40	
-75L		55	381	374	372	230	230		50	
-80L		65	381	374	372	230	230		52	
-100L		75	381	374	392	230	230		55	
-125L		95	411	404	429	250	260		75	
-150L		110	411	404	431	250	260		80	
-175L		132	421	404	451	260	260		82	
-200L		150	421	404	451	260	260		85	
-250L		190	471	429	448	300	284		120	
-300L		220	471	429	448	300	284		130	
-350L		260	491	454	489	310	310		170	
-400L	300	491	454	490	310	310	175			
-450L	335	511	510	487	330	320	180			
-500L	375	511	510	487	330	320	185			

TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN