

REACTORS

Autotransformers for Motor Starting [LV] (모터기동용 단권변압기 저압)

BHATRA-L Series







Technical Specifications

Line Voltage	220V / 380V / 440V
Operating Frequency	60Hz
Cooling System	Dry
Insulation Class	B Class

Typical Applications

Motor starting etc.



TO THE WORLD BUMHAN • WE MAKE FOR YOU • TO THE WORLD BUMHAN • WE MAKE FOR YOPU • TO THE WORLD BUMHAN • WE MAKE FOR YOU • TO THE WORLD BUMHAN

Selection Table

Type (형식명)	Specification(사양)		Dimension (외형치수, mm)					Weight (kg)	Remark
	Line Voltage(V)	Cap.(kW)	W	D	H	a	b		
BHATRA -30L	440V / 380V / 220V	22	401	340	393	250	210	13×30	40
-50L		37	401	350	408	250	220		50
-60L		45	401	360	413	250	230		55
-75L		55	421	384	433	250	240		65
-80L		65	421	389	448	250	240		75
-100L		75	421	394	458	250	250		80
-125L		95	451	404	473	280	260		90
-150L		110	451	414	483	280	270		100
-175L		132	501	427	453	300	280		110
-200L		150	501	439	453	300	290		120
-250L		190	561	449	496	330	300		140
-300L		225	561	464	496	330	320		155
-350L		265	601	492	501	330	330		175
-400L		300	601	492	536	330	330		185
-530L		400	601	499	591	350	340		240

TO THE WORLD BUMHAN • WE MAKE FOR YOU • TO THE WORLD BUMHAN • WE MAKE FOR YOPU • TO THE WORLD BUMHAN • WE MAKE FOR YOU • TO THE WORLD BUMHAN