

REACTORS

Condenser Series Reactors [LH+Discharge Coil] (콘덴서용 직렬리액터 고압:방전코일 포함)

BHSRAB-H Series







Technical Specifications

Circuit Voltage	3300V / 6600V
Operating Frequency	60Hz
Cooling System	Dry
Insulation Class	F Class
Reactance	6%
Standard	IEC, KS C

Typical Applications

Condenser etc.



TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN

Selection Table

Type (형식명)	Specification(사양)		Dimension (외형치수, mm)					Weight (kg)	Remark
	Voltage	Cap.(kVA)	W	D	H	a	b		
BHSRAB - 1.8H	6600V / 3300V	1.8	381	315	428	250	220	13×30	65
- 3H		3	401	325	435	270	230		75
- 4.5H		4.5	411	335	452	280	240		85
- 6H		6	491	345	488	340	250		100
- 9H		9	491	365	519	330	270		115
- 12H		12	541	365	509	370	270		120
- 15H		15	541	385	525	370	290		140
- 18H		18	541	395	545	370	300		155
- 24H		24	570	415	557	390	320		175
- 30H		30	610	432	615	410	330		200
- 36H		36	610	442	637	410	340		220

TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN ● WE MAKE FOR YOU ● TO THE WORLD BUMHAN